

## R7 WIND II HARNESS

### Description :

2 point Harness with work positioning belt.

This harness has been specifically designed for work at height in the wind onshore sector.

The harness is fitted with : sewn-in fall indicators (front and back), quick connect buckles on the chest, the belt and the leg straps, and 2 came adjustment buckles on the shoulders for an easy adjustment.

### Reference :

1035200 : R7 WIND II S/M

1035201: R7 WIND II L/XL

1035202 : R7 WIND II XXL

### Features :

#### Leg and waist webbing:

Black webbing 44 mm

Polyester with PTFE treatment (water repellent)

Breaking strength : > 2700 daN

#### Quick connect buckles (waist, leg and chest):

Material : steel

Breaking strength: 18 KN

#### Shoulder straps :

Material : aluminium

Breaking strength: 18 KN



Side Ds :

Material : Zinc coated steel  
Breaking strength : 22 KN

Dorsal buckle:

Material : Zinc coated steel  
Breaking strength : 22 KN

Side ring :

Stainless steel

Temperature:

-30°C to +50°C



Weight :

1035200 : 2.740 kg  
1035201 : 2.830 kg  
1035202 : 2.890 kg

EN 358 (1999) – EN 361(2002 )

***LAW of 19 MARCH 93***

PPE are products classified in category III, mortal risks, and as such they have to be the object of a periodic inspection for less than twelve months at the time of its use by the qualified person.

For more information, please contact our technical team at 02 48 52 40 42 or by e-mail [techniserv.hsp@honeywell.com](mailto:techniserv.hsp@honeywell.com)

HONEYWELL FALL PROTECTION FRANCE SAS

35-37 rue de la Bidauderie  
F - 18100 Vierzon - France

Tel : +33 2 48 52 40 40

Fax : +33 2 48 71 04 97

Web site : [www.honeywellsafety.com](http://www.honeywellsafety.com)