

Universe	Professional	
Туре	Verticality	
Category	Harnesses	
Subcategory	Fall arrest and work positioning harness	



VOLT® WIND

The fall arrest and work positioning VOLT WIND harness is very easily donned thanks to its EASYFIT design: a vest ensures the harness keeps its shape and the FAST automatic buckles on the waistbelt and leg loops allow the harness to be donned with both feet on the ground. The VOLT WIND harness' anatomical design and wide, semi-rigid waistbelt ensure comfort throughout the work day. Its LADDER CLIMB attachment point allows for ventral attachment of the fall-arrest trolley, thus ensuring optimal comfort during progression. It has wear protectors on the waistbelt and below the dorsal point to limit wear when moving about inside the wind turbine tower. It is certified to European and Russian standards.



The wide, semi-rigid waistbelt offers excellent lumbar support in work positioning situations. Additionally, its lightweight, breathable construction maximizes air flow.



For vertical progression with a rail or cable-based fall protection system, the LADDER CLIMB attachment point allows for ventral attachment of the trolley. It distributes the load on the waistbelt and thus ensures optimal comfort during progression. In case of a fall, this attachment point automatically moves upward to a sternal position to ensure a vertical post-fall body position.



The MGO connectors on ABSORBICA fall arrest lanyards can be stowed on each shoulder strap. The user is thus unhindered by the lanyard, and the connectors stay within reach. In case of a fall, a system releases the MGO connectors to allow the absorber to be deployed.



Fall indicators on the sternal and dorsal attachment points. If a fall indicator is visible after a fall, the harness must be retired.

Short Description

Fall arrest and work positioning harness for the wind power industry with attachment point for vertical progression on rail or cable

Selling Points

- It has wear protectors on the waistbelt and under the dorsal point to prevent strap wear when moving about inside the wind turbine tower
- Rapid donning thanks to the EASYFIT design:
- vest ensures the harness keeps its shape
- FAST automatic buckles on the waistbelt and leg loops allow the harness to be very easily donned, with both feet on the ground. These buckles retain their adjustment settings between donnings.
- · Comfortable throughout the work day:
- anatomical design is close-fitting, while giving optimal freedom of movement
- lightweight, breathable construction
- wide, semi-rigid waistbelt for excellent support
- for vertical progression with a rail or cable-based fall protection system, the LADDER CLIMB attachment point allows for ventral attachment of the fall-arrest trolley: it distributes the load on the waistbelt and thus ensures optimal comfort during progression. In case of a fall, this attachment point automatically moves upward to a sternal position to ensure a vertical post-fall body position.
- leg loop foam position can be adjusted for perfect positioning
- Easy to use:
- waistbelt and shoulder straps equipped with self-locking DOUBLEBACK buckles for quick and easy adjustment
- side attachment points can be folded down to prevent them snagging accidentally when not in use
- stowage system for the MGO connectors on fall arrest lanyards, on each shoulder strap. In case of a fall, this system releases the MGO connectors and allows the absorber to be deployed.
- fall indicators on the sternal and dorsal attachment points. If a fall indicator is visible after a fall, the harness must be retired.
- equipment loops, slots for CARITOOL tool holder and TOOLBAG tool pouch allow easy organization of work tools

Specification

- LADDER CLIMB attachment point: for attaching the trolley of a rail or cable-based fall protection system
- Sternal attachment point: for attaching a fall arrest system
- Dorsal attachment point: for attaching a fall arrest system
- Rear waistbelt attachment point: for attaching a restraint lanyard
- Side attachment points: for attaching a positioning lanyard for use in double mode
- Certification(s): CE EN 361, CE EN 358, EAC
- Material(s): nylon, polyester, aluminum, steel

Specifications by reference

Reference(s)	C72WFA 0	C72WFA 1	C72WFA 2
Size	0	1	2
Waist belt	65-80 cm	70-93 cm	83-120 cm
Leg loops	44-59 cm	47-62 cm	50-65 cm
Stature	160-180 cm	165-185 cm	175-200 cm
Weight	2055 g	2100 g	2180 g
Made in	RO	RO	RO
Guarantee	3 years	3 years	3 years
Packing	1	1	1
Case quantity	3	3	3
EAN	3342540103658	3342540103665	3342540103672

CARITOOL TOOLBAG LIFT Accessory(ies)

Related product(s)

GRILLON
ABSORBICA-Y European version
ABSORBICA-Y international version

MGO 110